

**8600 SERIES**  
Cylindrical  
Leverset  
ANSI GRADE 2



Meets ADA requirements. Specially designed for Barrier Free Application. Conforms with ANSI A156.2 Series 8600, Grade 2. Exceeds 400,000 cycles.



IC core is available

**F SERIES**

FreeWheeling clutch design. Free turning handle in the locked position without opening door, to deter breaking of the handle.

**8691 SC**



8671A BL



Concealed mounting screw  
Push in and turn button  
Cylindrical body provides great strength and durability, two sides spindle supporting mechanism eliminates lever wobble.  
Coil compression springs provide great strength and durability (interior)  
UL 3 Hour Rated 1/2" Throw deadlatch completely reversible for flat and beveled doors. Stainless steel latch bolt and faceplate.  
Patent Individual spring on each side to prevent lever sag, maintain reliability, reduce maintenance.  
Full length lever handle with 3/8" return  
High precision pick resistant 6-pin tumbler solid brass cylinder. Interchangeable with leading manufacturer cylinders. Must turn key one-quarter to remove and replace cylinder. Can be construction keyed and masterkeyed as required.

Lever style and finishes available



8551 SC

DIMENSIONS



8561 SC

DIMENSIONS



8571 SC

DIMENSIONS




8581 SC

DIMENSIONS



8591 SC


DIMENSIONS



Door Prep: Cross bore 2-1/8", Edge bore 1" Latch face 1"x2-1/4"  
BACKSET: Adjustable 2-3/8" or 2-3/4"  
Door Thickness: Adjustable 1-3/8" -- 2"  
Cylinder: 5-Pin or 6-Pin removable core. Schlage "C" keyway or Kwikset  
And other options available.  
Face plates: 1"x2-1/4" square corner. Standard. Round corner and other Options available.  
Strikes: 2-1/4" square corner standard. Standard corner and other options Available.  
Bolt: 1/2 throw. Nickel plated.  
ANSI/BHMA: A 156.2 Grade 2.

FUNCTIONS AVAILABLE (FW Indicates FreeWheeling/clutch design available. Prefix "FW" for FW SERIES)

8470(F87)



**Institutional Lock**  
Entry or exit by key only. Both levers always fixed.  
Prefix "F" for FW SERIES

8475




**Single Dummy Trim**  
Single dummy trim for one side of door.

8471(F81)



**Entrance/Office Lock**  
Turn/push button locking. Pushing and turning button locks outside lever requiring use of key until button is manually unlocked. Pushing button locks outside lever until unlocked with key or inside lever is turned. The inside lever is always unlocked providing emergency exit.  
Prefix "F" for FW SERIES

8476 (F84)




**Classroom Lock**  
The outside lever is locked or unlocked by key. When unlocked the lockset works as a passage set. When the lock is locked, you must use a key from outside to unlock the lockset. The inside lever is always unlocked providing emergency exit.  
Prefix "F" for F SERIES

8471A(F82)



**Entrance/Office Lock**  
Push button locking. Pushing button in inside lever locks outside lever until unlocked with key or turning inside lever. The inside lever is always unlocked providing emergency exit.  
Prefix "F" for FW SERIES

8477 (F77)



**Patio Lock**  
Deadlocking latchbolt operated by lever from either side. Outside lever is locked by push button inside and unlocked by rotating inside lever or closing door. The inside lever is always unlocked providing emergency exit.

8471B




**Entrance/Office Lock**  
Pushing button locks outside lever until unlocked with key or inside lever is turned. Turn/push button locking. Pushing and turning button locks outside lever forever even using a key until button is manually turned back. Do not use this lock in room without another entry in case of being locked outside carelessly. The inside lever is always unlocked providing emergency exit.

8478 (F80)



**Communicating Lock**  
Deadlocking latchbolt operated by lever from either side. Turning key in either lever locks or unlocks its own lever independently

8478B (F91)



**Store Door Lock**  
Both levers are locked or unlocked synchronously by key from either side.

8472 (F76)



**Privacy Lock**  
Latchbolt operated by lever from either side. Outside lever is locked by push button inside and unlocked by emergency release outside rotating inside lever or closing door. The inside lever is always unlocked providing emergency exit.  
Prefix "F" for FW SERIES

8479 (F89)




**Exit Lock**  
Deadlocking latchbolt operated by inside lever. Outside lever fixed. The inside lever is always unlocked providing emergency exit.

8473 (F75)




**Passage/Closet**  
Both levers are always unlocked from inside and outside

8479A




**Connecting Room/Exit lock**  
Deadlocking latchbolt operated from inside only. Blank plate outside.

8474 (F86)



**Storeroom Lock**  
Outside lever is fixed, entrance by key only. Every time the door closes this unit will lock. It cannot be left unlocked. The inside lever is always unlocked providing emergency exit  
Prefix "F" for FW SERIES

8479B



**Connecting Room/Exit Lock**  
The inside lever is locked or unlocked by key. When unlocked the lockset provides Exit. When locked the lockset stops Exit. Blank plate outside.